

# CMM PROBES AND SENSORS

HIGH PERFORMANCE FOR ANY APPLICATION






HEXAGON



HEXAGON



# CMM PROBES AND SENSORS

## A SOLUTION FOR ANY APPLICATION

When it comes to maintaining quality and driving inspection efficiency, choosing the right probe or combination of probes and sensors is crucial.


The wrong probe or sensor can cause production bottlenecks, rework and scrap. The right probe or sensor can drive throughput, maintain competitiveness, and enhance profitability. This document is designed to help manufacturers find the right probing system.

At the very minimum, any coordinate measuring machine (CMM) probing system should contribute to manufacturing productivity with robust performance and reliability. But since every application has different demands, manufacturers should be given the choice of a variety of probes and sensors primed for different measuring tasks.

Whether the job demands high accuracy, speed, flexibility, or a combination of the three, Hexagon Manufacturing Intelligence offers a comprehensive range of probes, probe heads, styli changers and accessories for CMMs to ensure manufacturers have the optimum solutions for their application.

Offering high durability for operation in industrial environments, Hexagon's probe and sensor systems enable users to enhance quality with:

- State-of-the-art technology
- Precise and reliable operation
- Maximum application flexibility and outstanding usability
- Quick and effective interchange of multiple sensors on one machine
- Extended modularity to configure optimised inspection systems according to productivity requirements



Non-contact sensors enable fast capture of workpiece data and greater application flexibility.



Innovative technologies enable best-in-class solutions for even the most challenging applications.



Thanks to the wide portfolio of accessories, sensors can be easily adapted to changing applications.



# PROBE HEADS

## INCREASING ACCESSIBILITY

Combined with a sensor, the probe head forms the heart of the CMM. Efficient inspection and data capture relies on using the right probe head, as this significantly influences the level of measuring speed and flexibility that can be achieved. Hexagon provides a variety of different types of probe heads to ensure manufactures have the solutions most suited to their application needs.

### **Manual Probe Heads**

Highly reliable and cost-effective, manual probe heads for touch trigger probes provide excellent basic capabilities. These heads enable the probes to be easily positioned to the required measurement points.

### **Automatic Indexing Probe Heads**

Enabling greater measuring versatility, these fully motorised probe heads are characterised by high speed operation and repeatability. They are equipped with a kinematic joint for multisensor capability, enabling use of tactile probes and laser scanners on one machine.

### **Continuous Probe Heads**

High-performance continuous wrist probe heads offer maximum flexibility, with virtually infinite angular positioning to capture parts. Combining high speed motion and compatibility with a range of probe types, these probe heads enable point-to-point measuring and scanning.

### **Heavy Duty Probe Heads**

Particularly suited for use with large or heavy probes, the Heavy Duty Probe Heads capture highly accurate measurements while carrying sensors further away from the machine ram than other probe heads.

# TACTILE PROBES

## HIGHEST PRECISION

Enabling very precise and repeatable 3D measurements, Hexagon's tactile probes are characterised by their long lifetime, high accuracy, ease of use and excellent access to difficult to reach measuring points.


Hexagon offers a wide range of scanning and touch trigger probes to ensure users have the right contact probing solution to meet uncertainty and repeatability requirements, as well as drive productivity with varying degrees of speed and accuracy.

### Scanning Probes

Scanning probes combine high precision and speed. With these probes, users can perform fast and accurate contour and form measurements as well as all standard measurements including discrete scanning, self-centring measuring and continuous high-speed scanning.

### Touch Trigger Probes


These probes perform fast and repeatable 3D point measurements. Thanks to different trigger forces and the compact design, touch trigger probes can be used very flexibly while being cost effective and easy to use.



HP-THD touch trigger probe - enables fast and highly accurate 3D point measurements. See page 20.



HP-S-X5 scanning probe - for highly accurate, continuous scanning measurements. See page 26.



HP-S-X1S scanning probe - for fast and flexible scanning measurements. See page 24.



# NON-CONTACT SENSORS

## FAST AND VERSATILE

Non-contact sensors greatly enhance a CMM's inspection capabilities. When measuring complex parts with difficult-to-access features or sensitive surfaces, non-contact sensors provide essential flexibility. Likewise, where quick measurements have to be done, non-contact sensors provide unparalleled speed.

### Laser Scanning Sensors


Laser scanning sensors allow rapid collection of high density point cloud data for inspection or reverse engineering. Hexagon laser scanning technologies deliver highest quality data under all environmental conditions, by automatically suppressing outliers caused by reflections or ambient light.

### Vision Sensors

The high-resolution camera sensors give measurement performance that tactical probes literally can't touch. A camera mounted directly on an automatic indexing probe head, vision sensors can be rotated in any position to inspect 2D features. This setup effectively replicates the flexibility and part access that can be achieved when using a vision system with a rotary table.

### Optical Sensors

Hexagon's HP-O scanning technology is based on frequency-modulated interferometric optical distance measurement. It combines a high scanning speed with increased measurement range, providing an alternative for high-precision tactile measurements when speed is important, parts are difficult to access with tactile probes or when parts may deform or be damaged by tactile probing.



HP-L-5.8 laser scanning sensor - affordable sensor for creation of point clouds on CMMs. See page 29.



HP-L-10.6 laser scanning sensor - flexible and adjustable sensor for creation of point clouds on CMMs. See page 28.



HP-O Flex sensor - highly accurate, fast and flexible non-contact measurements on CMMs. See page 31.

# RACKS AND SENSOR ACCESSORIES

## PUSHING FLEXIBILITY FURTHER

Hexagon's ranges of changer racks and sensor accessories allow users to adjust measurement capabilities for all kinds of applications, enhancing efficiency and flexibility.

### Racks

Hexagon's changer racks perform fast and repeatable exchanges of probe, extension and stylus configurations on the CMM probe head. These racks enable automatic multisensor utilisation within a single part program, helping users efficiently adapt to different workpiece requirements and reduce cycle times.

### Sensor Accessories

Challenging measurement applications often require more hardware features than what is possible with a standard configuration. With Hexagon's wide range of sensor accessories, such as extensions and adapters, it is possible to reach even the most difficult positions.



HR-R probe changer rack - enables quick exchange of TKJ sensors during the measurement program. See page 33.



HR-P probe module changer rack - exchange of HP-TM or HP-THD modules during part programs. See page 34.



HR-R probe changer rack - also compatible with long extensions and the heavy duty probe heads. See page 33.


# STYLI AND OTHER ACCESSORIES

## EXCELLENT PRODUCTS FOR OUTSTANDING MEASUREMENT RESULTS

To give production more leeway in to utilise tolerances, it is essential that manufacturing measurement technology and quality assurance systems use methods with the lowest possible measurement uncertainty. Measurement uncertainty is often determined the complete measuring system, including parts like stylus configurations or fixture solutions.

To meet maximum precision and quality requirements, all Hexagon Manufacturing Intelligence accessories are manufactured to the highest standards. There are available components for all kinds of coordinate measuring machines (CMMs), 3D laser trackers, portable measuring arms and probes for machine tools.

From fixtures to machine housings, from styli to cleaning supplies, Hexagon offers the most suitable accessories for even the most challenging applications.









HP-A58-T2.5

HP-L-5.8

NOTICE  
The HP must be off before connecting the HP to the system.  
© 2014 Intel Corporation





	PAGE
PROBE HEADS .....	12
TOUCH TRIGGER PROBES .....	20
SCANNING PROBES .....	24
NON-CONTACT SENSORS .....	28
RACKS .....	32
PROBE HEAD ACCESSORIES .....	38
CONFIGURATION CHARTS .....	42

## MANUAL PROBE HEAD

### HH-T



HH-T is a manually adjustable probe head that can be rotated into an infinite number of non-repeatable positions. Highly flexible yet cost-effective, the HH-T is the ideal tool for small and entry-level machines. Trigger force is manually adjustable to give optimal probing performance with many stylus configurations.

HH-T	
Part No. *	03939020
Probe repeatability 1D (2 Sigma)**	0.75 $\mu\text{m}$
Adjustable trigger force	0.1 to 0.3 N
Overtravel	X/Y = $\pm 20^\circ$ , Z = + 6 mm
Measuring directions	$\pm X, \pm Y, + Z$


\* For information about available sets, please see page 46

\*\* Test conditions: Stylus length 21 mm, force setting 0.12 N, touch speed 8 mm/sec.



## MANUAL PROBE HEADS

HH-MI | HH-MI-M



These manually indexable probe heads are capable of indexing in 15° increments and can achieve 168 unique positions without the need for requalification. The heads can be easily locked, unlocked and rotated with one hand.

The HH-MI features an integrated, high-precision touch trigger probe, which can be manually adjusted to allow for a wide range of stylus combinations.

The HH-MI-M features an M8 threaded connection, which enables users to mount a touch trigger probe on the head. When combined with a HP-TM touch trigger probe, probe modules can be exchanged with the HR-P probe module changer to give the flexibility of an automatic stylus change without the need for requalification.


	HH-MI	HH-MI-M
Part No. *	03939030	03939031
Angular rotation	A: 0° - 90°, B: ± 180°	A: 0° - 90°, B: ± 180°
Increments	15°	15°
Total number of positions	168	168
Position repeatability	1.5 µm	1.5 µm
Extensions	-	M8/M8, max. length 50mm
Probe repeatability 1D (2 Sigma)**	0.35 µm	-
Adjustable trigger force	0.1 to 0.3 N	-
Overtravel	X/Y = ± 20°, Z = + 6 mm	-
Measuring directions	± X, ± Y, + Z	-
Axis clamping	Manual, by two buttons on the probe head	Manual, by two buttons on the probe head

\* For information about available sets and accessories, please see page 46

\*\* Test conditions: Stylus length 21 mm, force setting 0.12 N, touch speed 8 mm/sec.

## AUTOMATIC 5° PROBE HEADS

HH-AS6-T5 | HH-AS6-M5 | HH-AS8-T5 | HH-AS8-M5 | HH-A-T5 | HH-A-M5



Offering high speed operation and high rotational torque, these probe heads are capable of indexing in steps of 5° and can achieve 3 024 unique positions.

The probe heads can either be mounted on the CMM with a shank or flange (HH-A version) or directly into the ram of the machine (HH-AS version for 80 mm or 65 mm rams).

The HH-A-M5 and HH-AS-M5 probe heads are fitted with an M8 threaded connection so users can leverage a touch trigger probe. The HH-A-T5 and HH-AS-T5 probe heads are fitted with a kinematic joint (TKJ), which makes them compatible with a wide range of Hexagon TKJ sensors such as scanning probes or laser scanners.


	HH-AS6-T5 TKJ 5°	HH-AS6-M5 M8 5°	HH-AS8-T5 TKJ 5°	HH-AS8-M5 M8 5°	HH-A-T5 M8 5°	HH-A-M5 M8 5°
Part no. *	03939260	03939280	03939270	03939290	03939450	03939400
Indexing angle	5°	5°	5°	5°	5°	5°
A axis	+ 90° to - 115°	+ 90° to - 115°	+ 90° to - 115°	+ 90° to - 115°	+ 90° to - 115°	+ 90° to - 115°
B axis	± 180°	± 180°	± 180°	± 180°	± 180°	± 180°
Total number of positions	3 024	3 024	3 024	3 024	3 024	3 024
Rotation speed	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.
Positioning repeatability	< 0.5 µm at 100 mm from the centre of A axis rotation					
Max. recommended drive torque	0.6 Nm	0.6 Nm	0.6 Nm	0.6 Nm	0.6 Nm	0.6 Nm
Max. extension length	300 mm	300 mm	300 mm	300 mm	300 mm	300 mm
Weight	880 g	880 g	900 g	900 g	780g	780g
Head mounting	65 mm ram	65 mm ram	80 mm ram	80 mm ram	Shank/flange	Shank/flange
Probe mounting	TKJ (multiwire)	M8 thread (2 wires)	TKJ (multiwire)	M8 thread (2 wires)	TKJ (multiwire)	M8 thread (2 wires)
Head controller	HH-C-V2.1 / HH-CA-V2.1 (with HR-R probe changer rack)					

\* For information about available sets and adapters, please see pages 46 - 47



## AUTOMATIC 7.5° PROBE HEADS

HH-AS8-T7.5 | HH-AS8-M7.5 | HH-A-T7.5 | HH-A-M7.5




The HH-A-M7.5 and HH-AS-M7.5 motorised indexable probe heads feature an M8 threaded connection to enable the mounting of a touch trigger probe. The HH-A-T7.5 and HH-AS8-T7.5 probe heads are fitted with a kinematic joint (TKJ), which enables multisensor capabilities.

	HH-AS8-T7.5 TKJ 7.5°	HH-AS8-M7.5 M8 7.5°	HH-A-T7.5 TKJ 7.5°	HH-A-M7.5 M8 7.5°
Part no. *	03939362	03939363	03939360	03939361
Indexing angle	7.5°	7.5°	7.5°	7.5°
A axis	+ 105° to - 0°	+ 105° to - 0°	+ 105° to - 0°	+ 105° to - 0°
B axis	± 180°	± 180°	± 180°	± 180°
Total number of positions	720	720	720	720
Rotation speed	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.	90° in 2 sec.
Positioning repeatability	< 0.5 µm at 100mm from the centre of A axis rotation			
Max. recommended drive torque	0.6 Nm	0.6 Nm	0.6 Nm	0.6 Nm
Max. extension length	300 mm	300 mm	300 mm	300 mm
Weight	900 g	900 g	800g	800g
Head mounting	80 mm ram	80 mm ram	Shank/flange	Shank/flange
Probe mounting	TKJ (multiwire)	M8 thread (2 wires)	TKJ (multiwire)	M8 thread (2 wires)
Head controller	HH-C-V2.1 / HH-CA-V2.1 (with HR-R probe changer rack)			

\* For information about available sets and adapters, please see pages 46 - 47

## AUTOMATIC 2.5° PROBE HEADS

HH-A-T2.5 | HH-AS8-T2.5



Thanks to a sophisticated drive system, these probe heads feature a large number of indexable positions and very high rotational torque.

The HH-A-T2.5 range is capable of indexing in 2.5° increments and can achieve 12 240 unique positions. They feature an embedded controller, capacitive crash protection and positioning by use of a hirth gear.

The probe heads can either be mounted on the CMM with a shank or flange (HH-A version) or directly into the ram of the machine (HH-AS version for 80 mm rams).


The probe heads' TKJ can be connected to a multiwire to enable full multisensor capabilities

	HH-A-T2.5 TKJ 2.5°	HH-AS8-T2.5 TKJ 2.5°
Part no. *	03939420	03939422
Indexing angle	2.5°	2.5°
A axis	± 105°	± 105°
B axis	± 180°	± 180°
Total number of positions	12 240	12 240
Rotation speed	90° in 2.5 s	90° in 2.5 s
Positioning repeatability	All: < 0.5 µm at 100mm from the centre of A axis rotation	
Max. recommended drive torque	1.4 Nm	1.4 Nm
Max. extension length	450 mm	450 mm
Weight	1 600 g	1 650 g
Head mounting	Shank/flange	80 mm ram
Probe mounting	TKJ (multiwire)	TKJ (multiwire)
Head controller	All: HH-C-V2.1 / HH-CA-V2.1 (with HR-R probe changer rack)	

\* For information about available sets and adapters, please see pages 46 - 47

## AUTOMATIC 2.5° HDKJ PROBE HEADS

HH-A-H2.5 | HH-AS8-H2.5



Offering the highest level of measuring flexibility, these probe heads are capable of indexing in 2.5° increments and can achieve 20 736 unique positions. They feature an embedded controller, capacitive crash protection to prevent probe damage and a hirth gear for highly accurate positioning of the probe.

The probe heads can either be mounted to the CMM with a shank or flange (HH-A version) or directly into the ram of the machine (HH-AS version for 80 mm rams). Laser scanners and scanning probes can be supported further from the axis of rotation (750 mm) than with conventional heads due to the combination of extreme rotational torque and the heavy duty kinematic joint (HDKJ) adapter.


The HDKJ can be changed either manually without the need for requalification or automatically with the HR-R probe changer rack fitted with the optional HR-RH heavy duty module.

	HH-A-H2.5 HDKJ 2.5°	HH-AS8-H2.5 HDKJ 2.5°
Part no. *	03939430	03939431
Indexing angle	2.5°	2.5°
A axis	± 180°	± 180°
B axis	± 180°	± 180°
Total number of positions	20 736	20 736
Rotation speed	90° in 2.5 s	90° in 2.5 s
Positioning repeatability	All: < 0.5 µm at 100mm from the centre of A axis rotation	
Max recommended drive torque	1.7 Nm	1.7 Nm
Maximum extension length	750 mm	750 mm
Weight	1 550 g	1 600 g
Head mounting	Shank/flange	80 mm ram
Head controller	All: HH-C-V2.1 / HH-CA-V2.1 (with HR-R probe changer rack)	

\* For information about available sets and adapters, please see pages 46 - 47

## CONTINUOUS PROBE HEAD

### HH-ACW-43MW



Offering the ultimate in flexibility, the HH-ACW-43MW multi-axis continuous probe head enables fast and accurate orientation of probes in any probing direction in space. Alongside the ability to handle standard extensions up to 600 mm in length, the continuous positioning of rotary axes (in unlimited angular positions) enables complete access to the part being measured.

The exclusive probe changer rack allows for automatic exchange of extensions and adapters, ensuring ideal flexibility. With its multiwire adapter, the HH-ACW-43MW continuous probe head is compatible with the most popular probes and styli/probe changer racks, allowing point-to-point and scanning measurements.

The HH-ACW-3AA can be configured with integrated third axis for optimised use of non-contact sensors.

HH-ACW-43MW	
Part no.	G30481300
Useful angular stroke (Roll axis)	$\pm 180^\circ$
Useful angular stroke (Pitch axis)	$\pm 170^\circ$
Rotation speed	1 rad/sec.
Acceleration	10 rad/sec. <sup>2</sup> / 0,14 arc <sup>l</sup>
Positioning repeatability	$1 \times 10^{-5}$ rad
Weight	3.5 kg
Max. tool weight	1.5 kg
Max. applied torque	2 Nm
Adapters	HA-ACW-AA, HA-ACW-3AA
Extensions	E200-mw, E330-mw, E570-mw, HP-T-RP, HP-T, HP-TM
Changer racks	HR-ACW-AC, HR-P




HEXAGON

0 10 20 30 40 50

05 00 05 10 15 20 25 30

## TOUCH TRIGGER PROBES

### HP-THD



Built from cutting-edge technology, the HP-THD touch trigger probe is particularly well-suited for applications with tight tolerances, as well as tasks that require both high speed measurement and a high level of point density. The HP-THD delivers highly accurate touch trigger probing with styli builds of up to 100 mm. It offers high-precision repeatability and low 3D form error thanks to a highly innovative optomechanical design capable of detecting nanometric movements in the X, Y and Z directions.

With its robust design and long module life, the HP-THD reduces downtime and enables additional time and cost savings with its high performance and fast stylus and module changes.

Standard probes employ a mechanical switch to create probing points that generate variable force dependent on the direction of probing. This force leads to small form errors sometimes called 'lobing'. The mechanical design of the HP-THD touch trigger probe saves potential rework time by overcoming this force to deliver very low lobing in all six probing directions.

	HP-THD-MF Medium Force	HP-THD-SF Standard Force
Part no. (Probe Module)	03939604	03939603
Kit no. (Probe module and body)	03939622	03939621
Part no. (Probe Body)	03939601	03939601
Overtravel force (XY plane)	0.71 N max	0.3 N max
Overtravel force (Z plane)	2.24 N	1.14 N
Mounting	M8 with active 1 wire connection	M8 with active 1 wire connection
Suitable interface	HH-C-V2.1 or higher	HH-C-V2.1 or higher
Trigger force	0.07 N (XY plane)/0.78 N (Z plane)	0.07 N (XY plane)/0.78 N (Z plane)
Probing directions	6 Way $\pm X$ , $\pm Y$ and $\pm Z$	6 Way $\pm X$ , $\pm Y$ and $\pm Z$
Form error	0.8 $\mu\text{m}$ (2D)/1.3 $\mu\text{m}$ (3D)	0.8 $\mu\text{m}$ (2D)/1.3 $\mu\text{m}$ (3D)
Unidirectional repeatability $2\sigma^*$	0.3 $\mu\text{m}$	0.3 $\mu\text{m}$
Weight (probe and body)	21.6 g	21.6 g
Stylus mounting	M2	M2
Module changer rack	HR-P6	HR-P6
Max. extensions	750 mm (HH-A-H2.5) 300 mm (HH-A-T5 or HH-A-T7.5) 450 mm (HH-A-T2.5)	750mm (HH-A-H2.5) 300mm (HH-A-T5 or HH-A-T7.5) 450mm (HH-A-T2.5)

\*Test conditions: Straight stylus, length 10 mm, touch speed 5 mm/sec.



## TOUCH TRIGGER PROBE

## HP-TM



HP-TM is a compact and modular five way touch trigger probe, ideal for fast and high accuracy measurement.

The two piece design comprises of the probe body and a detachable probe module. The body and module are connected together by a highly repeatable kinematic magnetic coupling. The modules can be quickly changed either manually or automatically without the need to recalibrate the probe.

The stylus modules are available in four versions, each giving a different trigger force to ensure high accuracy. The HP-TM system can be easily retrofitted and is compatible with a range of touch trigger controllers, extensions and accessories.

	HP-TM-LF Low Force	HP-TM-SF Standard Force	HP-TM-MF Medium Force	HP-T-EF Extended Force
Part no. (Probe Module)	03939170	03939171	03939172	03939173
Part no. (Probe Body)	03939174	03939174	03939174	03939174
Pretravel variance	± 0.6 µm	± 0.8 µm	± 1.00 µm	± 2.00 µm
Trigger force	0.055 N at 10 mm	0.08 N at 10 mm	0.10 N at 25 mm	0.10 N at 50 mm
Repeatability 1D (2 Sigma)*	< 0.35 µm	< 0.35 µm	< 0.5 µm	< 0.65 µm
Probing directions	± X, ± Y, + Z	± X, ± Y, + Z	± X, ± Y, + Z	± X, ± Y, + Z
Probe mounting	M8	M8	M8	M8
Stylus mounting	M2	M2	M2	M2
Max. stylus length	30 mm	50 mm	60 mm	60 mm
Weight (Probe and body)	11 g	11 g	11 g	11 g

\*Test conditions: Stylus length 21 mm, Force setting 0.12 N, Touch speed 8 mm/sec.

## Contents of HP-TM Kits

	Kit 1	Kit 2	Kit 3	Kit 4	Kit 5	Kit 6	Kit 7	Kit 8	Kit 9	Kit 10	Kit 11
Part no.	03939175	03939210	03939211	03939212	03939213	03939214	03939215	03939216	03939217	03939218	03939219
HP-TM-LF	1 pc.							1 pc.			
HP-TM-SF	1 pc.	2 pc.	1 pc.	1 pc.					1 pc.		
HP-TM-MF	1 pc.		1 pc.		2 pc.	1 pc.				1 pc.	
HP-TM-EF	1 pc.			1 pc.		1 pc.	2 pc.				1 pc.
HP-TB probe body	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.

## TOUCH TRIGGER PROBE

### HP-T



Cost-effective and sturdy, the HP-T touch trigger probe is a durable and compact five way touch trigger probe, offering high accuracy and measuring flexibility.

The HP-T is available in one of four variations, each providing a different trigger force (ranging from low to extended force).


The touch trigger probe is fitted with a M8 threaded connection, enabling compatibility with a wide range of manual and automatic probe heads. A kinematic adapter can also enable automatic module changes with the HR-R changer rack.

	HP-T-LF Low Force	HP-T-SF Standard Force	HP-T-MF Medium Force	HP-T-EF Extended Force
Part no.	03939070	03939071	03939072	03939073
Pre travel variance	± 0.6 µm	± 0.8 µm	± 1.00 µm	± 2.00 µm
Trigger force	0.055 N at 10 mm	0.08 N at 10 mm	0.10 N at 25 mm	0.10 N at 50 mm
Repeatability 1D (2 Sigma)*	< 0.35 µm	< 0.35 µm	< 0.5 µm	< 0.65 µm
Probing directions	± X, ± Y, +Z	± X, ± Y, +Z	± X, ± Y, +Z	± X, ± Y, +Z
Probe mounting	M8	M8	M8	M8
Stylus mounting	M2	M2	M2	M2
Max. stylus length	30 mm	50 mm	60 mm	60 mm
Weight	9.5 g	9.5 g	9.5 g	9.5 g

\*Test conditions: Stylus length 21 mm, Force setting 0.12 N, Touch speed 8mm/s

## TOUCH TRIGGER PROBE

### HP-T-RP



Compatible with all Hexagon bridge and sheet metal measuring machines, the HP-T-RP is a robust and accurate touch trigger probe designed to be used in even the harshest industrial environments.


The rugged nature of the probe makes it ideally suited to work with both robots and portable equipment. The accuracy can be optimised by manually adjusting the trigger force for the required application.

HP-T-RP	
Part no.	03939350
Probing directions	$\pm X, \pm Y, + Z$
Stylus force	0.11 N to 0.30 N
Repeatability 1D (2 Sigma)	10 rad/sec.
Probe mounting	M8
Stylus mounting	M3
Overtravel	X/Y: $\pm 22.0^\circ$ , Z: 5.5 mm (with 0.11 N), 2.0 mm (with 0.30 N)
Max stylus length	100 mm
Weight	43 g

\*Test conditions: Stylus length 21 mm, Force setting 0.12 N, Touch speed 8mm/sec.

## SCANNING PROBES

HP-S-X1S | HP-S-X1H | HP-S-X1C



HP-S-X1 are highly accurate 3D scanning probes that can rapidly and automatically collect thousands of data points for the complete and precise evaluation of all part features, including form, location and size.

HP-S-X1 scanning probes support both single point probing and continuous scanning. HP-S-X1 probes provide simultaneous and unclamped probing in all axes, always orthogonal to the contact surface.

The probes' optional self-centring mode are particularly useful for measuring gears.

HP-S-X1S and HP-S-X1H are equipped with a kinematic joint, which allows for automated probe changes with the HR-R probe changer rack. Magnetic stylus holders enable fast and repeatable stylus changes using the HP-S-X styli changer rack or the three port unit of the HR-R probe changer rack.

HP-S-X1C is equipped with a dovetail connector for mounting directly into the ram of the machine.

	HP-S-X1S	HP-S-X1H	HP-S-X1C
Part no.	M00-114-040-000	M00-114-042-000	M00-114-043-000
Probe type	Analogue	Analogue	Analogue
Probe connector	TKJ (kinematic joint)	TKJ (kinematic joint)	Centre mounted
Dimensions	Ø 30 x 109 mm	Ø 30 x 109 mm	Ø 30 x 95 mm
Weight	100 g	100 g	100 g
Resolution	< 0.1 µm	< 0.1 µm	< 0.1 µm
Measuring range	± 2 mm in all axes	± 2 mm in all axes	± 2 mm in all axes
Linear stiffness	1.2 N/mm	1.2 N/mm	1.2 N/mm
Stylus holder thread	M3	M3	M3
Max. stylus weight (Including stylus clamping)	20 g	33 g	33 g
Max. stylus length	Axial: Up to 115 mm Lateral: Up to 20 mm	Axial: Up to 225 mm Lateral: Up to 100 mm	Axial: Up to 225 mm Lateral: Up to 100 mm

## SCANNING PROBE

### HP-S-X3



Compact, fast and accurate, the HP-S-X3 offers effective single point probing in all standard metrology tasks as well as continuous high-speed-scanning for form and profile inspection of complex geometric elements (for example, cylinder gears, worm gears, turbine blades, worm screws, and more).

The HP-S-X3's highly sensitive sensor and large linear measuring range ensures excellent precision and extends application possibilities.

HP-S-X3 can carry up to 360 mm long probing extensions. Probe trigger force is measured by high resolution linear variable differential transducers (LVDT), allowing the correct compensation for stylus deflection even when long extensions are fitted and automatic measurement in a direction orthogonal to the part.

	HP-S-X3
Part no.	M00-114-039-000
Probe type	Analogue
Probe interface	TKJ (kinematic Joint)
Dimensions	Ø 64 x 89 mm
Weight	270 g
Resolution	< 0.1 µm
Measuring range	± 1 mm in all axes
Overtravel range	± 1.25 mm in all axes
Linear stiffness	6 N/mm
Stylus joint	M5
Max. stylus weight	150 g (incl. stylus clamping)
Max. stylus length	Up to 360 mm

## SCANNING PROBES

### HP-S-X5 | HP-S-X5HD



The HP-S-X5 fixed scanning probe is optimised for measuring the tightest of tolerances. Offering very high precision and repeatability, HP-S-X5 enables true 3D probing, capable of simultaneously measuring in the X, Y and Z directions. This analogue probe is well-suited to performing single point probing and continuous high-speed scanning for profile and shape error inspection of complex geometric parts.

The HP-S-X5's motor-free design means there are no heat sources within the probe, helping to ensure results are unaffected by temperature changes. The probe is protected by its robust design and effective anti-collision system, reducing downtime.

The probe reduces errors in results with its compensation system that accurately adjusts for the stylus deflection even when long extensions are fitted.

HP-S-X5's dovetail connection allows fast and easy change of the probe when performing maintenance work.

As an option, a workpiece temperature sensor (WTS) can be swapped into the probe automatically.

	HP-S-X5	HP-S-X5HD*
Part no.	M00-114-031-000	M00-114-024-000
Probe type	Analogue	Analogue
Position	Centre mounted	Centre mounted
Probe interface	Dovetail connector	Dovetail connector
Dimensions	Ø 84 x 191 mm	Ø 84 x 191 mm
Weight	1 080 g	1 080 g
Resolution	< 0.1 µm	< 0.1 µm
Measuring range	± 1 mm in all axes	± 1 mm in all axes
Overtravel range	± 2 mm in all axes	± 2 mm in all axes
Linear stiffness	5 N/mm	5 N/mm
Stylus joint	M5	M5
Max. stylus weight	500 g (Incl. Stylus clamping)	650 g (Incl. Stylus clamping)
Max. stylus length	Up to 500 mm	Up to 800 mm
Collision protection	Standard	Standard
Air supply	0.5 MPa	0.5 MPa
Part temperature sensor	Optional	Optional
Profiler R (tactile roughness sensor)	Not compatible	Optional

\* Only available on CMMs Leitz PMM-Xi and Leitz Reference Xi in combination with QUINDOS metrology software



## TEMPERATURE SENSOR FOR HP-S-X5



The exchangeable HP-S-X5 temperature sensor enables fast automatic measurement of workpiece temperature.

By using the various modules available (joints and extensions), users can assemble any configuration necessary to measure temperature, even on inclined surfaces. This allows the sensor to be set up to fulfil the unique requirements of any measuring task.


The sensor can be stored in a rack just like any other stylus configuration and can be loaded automatically within a part program. An integrated electrical interface connects the sensor with the probe head and the electronics of the CMM.

### PART TEMPERATURE SENSOR FOR HP-S-X5

M00-741-073-000	Exchangeable Temperature Sensor Basis Kit (incl. clamping and sensor), calibrated
M00-741-079-000	Exchangeable Temperature Sensor Complete Kit (incl. clamping, sensor, joint, extension), calibrated
M00-741-062-150	Extension
M00-741-062-050	Joint

## LASER SCANNERS

HP-L-10.6T | HP-L-10.6A | HP-L-20.8T



HP-L-10.6 and HP-L-20.8T laser scanning sensors deliver maximum performance for complex surfaces and workpieces made of materials that are difficult to measure. These versatile laser scanners record precisely even at the highest speeds and are particularly well-suited to inspecting the characteristics of thin-walled components, sheet metal parts, freeform surfaces, and reverse engineering. The accuracy of the sensors is certified to the standard ISO 10360-8:2013.

Offering excellent measurement flexibility, the laser line width can be varied as needed from 24 mm to 124 mm (HP-L-10.6) and up to 220 mm (HP-L-20.8). The laser power is automatically adjusted in real time.

The HP-L-10.6T can be used in almost all Hexagon Manufacturing Intelligence CMMs. The HP-L-10.6A can be used on a CMM with an AJ adapter. The HP-L-20.8T is primarily offered on a portable measuring arm, but can also be used on Hexagon CMMs with an adapter.

**Warming post for HR-R Probe Changer Rack 03939507**

**Manual warm-up station (TKJ) G32438600 / Manual warm-up station (autojoint) G3243800**

**Set of 4 TKJ Angular Adapters (to be used only with HP-L-10.6T) 03969394**

HP-L-20.8T on a CMM the following additional items should be ordered: **HP-LC-210 Controller (P/N 03939534), 1x Power unit 24 VDC with cables (03939505), 1x TKJ key (03969357), 1x HA-C-T Adapter TKJ for HP-L-20.8T (03939526) or 1x HA-C-A Adapter AJ for HP-L-20.8T (03939527), 1x Sphere (03939542)**


	HP-L-10.6T TKJ Connection	HP-L-10.6A Autojoint Connection	HP-L-20.8T TKJ Connection
Part no.	03939500	03939501	03939535
Size L x W x H	134 x 72 x 60 (98) mm	134 x 72 x 60 (87) mm	137 x 76 x 85 mm
Weight	379 g	360 g	410 g
Standoff and depth (Z)	170 ±30 mm	170 ±30 mm	180 ±40 mm
Measuring accuracy ISO 10360-8:2013* (GLOBAL CMM except GLOBAL eXtra)			
PForm.Sph.D95%:Tr:ODS (MPL) Probe dispersion value	34 µm	34 µm	36µm
PForm.Sph.1x25:Tr:ODS (MPE) Probing form error	22 µm	22 µm	25µm
Lines per second (max.)	53 Hz	53 Hz	100 Hz
Laser line width (at mid-field)	24, 60 or 124 mm	24, 60 or 124 mm	25, 51, 63, 130 or 220 mm
Data rate (max.)	30 000 pts/sec	30 000 pts/sec	150 000 pts/sec
Ambient light of the sensor	40 000 lx	40 000 lx	40 000 lx
Laser protection class	2 ICE 60825 -1 :2007	2 ICE 60825 -1 :2007	2 ICE 60825 -1 :2007
Laser	Visibly red, (690 nm)	Visibly red, (690 nm)	Visibly red, (690 nm)
Operating temperature	+5 to +45°C (41 to 113°F)	+5 to +45°C (41 to 113°F)	+5 to +45°C (41 to 113°F)
Declared accuracy temperature range	+15 to +32°C (59 to 90°F)	+15 to +32°C (59 to 90°F)	+15 to +32°C (59 to 90°F)
Relative humidity	90% non-condensing	90% non-condensing	90% non-condensing
Power supply	All: DC 18 to 28 V, 170 to 200 mA, protected against polarity reversal		
Protection against dust and water	All: IP64 (IEC 60529) except for warm-up connection		
Storage temperature	All: -25 to +70 °C (-13 to 158° F)		
Laser safety			

\* Values include expanded measurement uncertainty according to ISO/TS 17865:2016.

Measured using a manufacturer supplied sphere- and plane artefact, each certified by an independent accredited lab.

**LASER SCANNERS**

HP-L-5.8T | HP-L-5.8A



HP-L-5.8T

The HP-L-5.8 laser scanning sensor makes it easy and affordable to begin creating point clouds on a CMM. The fixed-line blue laser can measure a wide range of surfaces, from very dark through to very shiny. The rugged and compact design makes it ideal for laser scanning on smaller CMMs and where accessibility is restricted.

The HP-L-5.8T is equipped with Hexagon’s kinematic joint, making it compatible with Hexagon probe heads and accessories, including automatic sensor changing racks and extensions.

- Warming post for HR-R Probe Changer Rack 03939507
- Manual warm-up station (TKJ) G32438600 / Manual warm-up station (autojoint) G3243800
- Set of 4 TKJ Angular Adapters (to be used only with HP-L-5.8T) 03969394

	HP-L-5.8T TKJ Connection	HP-L-5.8A Autojoint Connection
Part no.	HP-L-5.8T-SYSTEM	HP-L-5.8A-SYSTEM
Size L x W x H	116 x 62 x 86.5 (106.5) mm	116 x 62 x 81 (101) mm
Weight	380 g	360 g
Standoff and depth (Z)	140 ± 40 mm	140 ± 40 mm
Measuring accuracy ISO 10360-8:2013* (GLOBAL CMM except GLOBAL eXtra)		
PForm.Sph.D95%:Tr:ODS (MPL) Probe dispersion value	34 µm	34 µm
PForm.Sph.1x25:Tr:ODS (MPE) Probing form error	22 µm	22 µm
Lines per second (max.)	40 Hz	40 Hz
Laser line width (at mid-field)	47 mm	47 mm
Data rate (max.)	36,000 pts/sec	36,000 pts/sec
Ambient light of the sensor	5 000 lx	5 000 lx
Laser protection class	2 (IEC 60825-1: 2014)	2 (IEC 60825-1: 2014)
Laser	Visible blue - 450 nm	Visible blue - 450 nm
Operating temperature	5 to 45° C (41° to 113°F)	5 to 45° C (41° to 113°F)
Declared accuracy temperature range	15 to 32° C (59° to 90°F)	15 to 32° C (59° to 90°F)
Relative humidity	90% non-condensing	90% non-condensing
Power supply	All: DC 18 to 28 V, 170 to 200 mA, protected against the polarity reversal	
Protection against dust and water	All: IP64 (IEC 60529) (except for warm-up terminal)	
Storage temperature	All: -25° to +70° C (-13° to +158° F)	
Laser safety		

\* Values include expanded measurement uncertainty according to ISO/TS 17865:2016. Measured using a manufacturer supplied sphere- and plane artefact, each certified by an independent accredited lab.

## VISION SENSOR

### HP-C-VE



The versatile HP-C-VE vision sensor is a general purpose image analysis tool for enhancing the measurement capabilities of a CMM.

The HP-C-VE contains a customisable illumination system, making it a self-contained measuring system, suitable for a wide range of applications. Due to its general-purpose nature, the HP-C-VE sensor uses fixed magnification and is designed for taking data points in a static condition. It provides oblique overhead illumination of the feature being inspected.

The HP-C-VE is compatible with the HR-R probe changer rack. This system allows the CMM to automatically change the sensor being used, enabling the HP-C-VE to be integrated within multiple sensor part programs while removing the need for any operator intervention.

HP-C-VE	
Part no.	CMMV-Set
Field of view (FOV)	Approx. 6 mm x 5 mm (on the work piece being inspected) Area: >35 mm <sup>2</sup>
Optical magnification	The image at the CCD is 75% of the Field of view (FOV) (on the workpiece)
Object to camera standoff	75 mm
Illumination	LED-illuminator Oblique and targeted at the optical plane centre
Type	High intensity green for optimum reflection
Inner LED ring	4 radially spaced at 90° at 0° inclination
Outer LED ring	8 radially spaced at 45° and at 16° inclination (The spacing of these 8 is also staggered radially 22.5° to the 4 LED pattern)
Selective illumination	Rings are split into four segments – intensity of both rings can be adjusted independently

#### HP-C-VE Specification according to ISO-10360-7:2011

ISO 10360-7:2011 specifications are valid for the vertical orientation (A0B0 tip)

Acceptance Test	Symbol	Specificaton (µm)
Probing error (with CMM motion)	PF2D,MPE	10.0
Probing error of the imaging probe (without CMM motion)	PFV2D,MPE	6.0
Imaging probe length measurement error (without CMM motion, L in mm)	EUV,MPE	4.0 + 2.0 L

**OPTICAL SENSOR**  
HP-O FLEX



HP-O delivers excellent speed, precision, and part access. This sensor combines highly accurate interferometric, optical HP-O technology with the flexibility of an automatic indexing probe head, indexing in steps of 2.5° and capable of achieving up to 12 240 unique positions. The probe head offers high speed operation and high rotational torque.

**OPTICAL SENSOR**  
HP-O HYBRID




This fixed sensor system enables users to combine optical and tactile styli in one configuration. The high precision interferometric, optical HP-O technology offers accuracy and reliability comparable to tactile scanning probes, while also delivering the higher scanning speed, increased measurement range and flexibility of non-contact measurement.

	<b>LASER</b> <b>2</b>		<p>LASER RADIATION DO NOT LOOK INTO THE BEAM <b>CLASS 2 LASER PRODUCT</b> 620-690 nm / 1 mW cw   1500-1600 nm / 10 mW max. applied standard: IEC 60825-1:2014</p>
--	--------------------------	--	---

## PROBE CHANGER RACK

### HR-ACW-AC



The HR-ACW-AC probe changer rack, in combination with the HH-ACW-43MW probe head, enables automatic repeatable exchange of all Hexagon adapters/extensions during execution of the measuring program. The modular concept of the changer rack allows for configuration of a number of stations.

The rack is available for horizontal or vertical arm CMMs. It can be equipped with a programmable logic controller (PLC), which is used to automatically identify if slots are free or filled.

CHANGER RACK FOR HORIZONTAL ARM CMM				
Part no.	Part description	Weight	Ports	Variation
G32631100	Stand of HR-ACW-AC	80 kg	Max. 8	
G32631201	Station for HH-ACW-43MW adapter and extensions			Without PLC
G32451600	Station for HH-ACW-3AA adapter with warm up function ARM1			Without PLC
G32451700	Station for HH-ACW-3AA adapter with warm up function ARM2			Without PLC
G32435901	Station for HH-ACW-43MW adapter and extensions			With PLC
G32451200	Station for HH-ACW-3AA adapter with warm up function ARM1			With PLC
G32451300	Station for HH-ACW-3AA adapter with warm up function ARM2			With PLC


\* Air supply requirements: > 0.45MPa < 1.0MPa (rated working pressure)

CHANGER RACK FOR VERTICAL ARM CMM				
Part no.	Part description	Ports	Variation	
G32432900	Stand for HR-ACW-AC*	Max. 5	Without PLC	
G32633000	Station for HH-ACW-43MW adapter and Extensions		Without PLC	
G32633100	Station for HH-ACW-3AA adapter with warm up function		Without PLC	
G32436900	Stand for HR-ACW-AC*	Max. 5	With PLC	
G32437300	Station for HH-ACW-43MW adapter and extensions		With PLC	
G32439500	Station for HH-ACW-3AA adapter with warm up function		With PLC	

\* Air supply requirements: > 0.45MPa < 1.0MPa (rated working pressure)

## PROBE CHANGER RACK

### HR-R



Saving time and increasing flexibility, the HR-R is an automatic probe changer rack that uses Hexagon's unique TKJ connector to exchange probes and extensions to and from the HH-A-T series of probe heads. The probe exchange is performed both quickly and accurately with no need for requalification. The HR-R is modular and can be easily customised to suit any application.

Part No.	Part description	Ports	L (mm)	H (mm)
03939110	HR-R3	3	220	350
03939111	HR-R5	5	304	350
03939112	HR-R9	9	472	350
03939192	HR-RP-2	Additional 2		
03939091	HR-RA-40	Additional active port	40	
03939092	HR-RA-65	Additional active port (for HP-C-VE, HP-L, HP-S-X3T)	65	
03969370	Rising block		100	
03969371	Rising block		500	
052901	Adjustable feet			
03939093	HR-RH Module	Module for HA-HT and HA-HM Adapter		

## PROBE MODULE CHANGER RACK

### HR-P




The HR-P is a passive probe module changer rack; modules are exchanged by the CMM under the control of the measuring software. The HR-P rack is also designed to store probe modules safely and securely, providing them with protection from airborne contamination. The rack is available with two, four or six ports and in two different heights: 90 mm and 150 mm. There is also an optional module that can be combined with the HR-R probe changer rack to enable module exchanges without the need of an extra rack on the CMM.

	HR-P2-90	HR-P2-150	HR-P4-90	HR-P4-150	HR-P6-90	HR-P6-150	HR-PA-2
Part no.	03939185	03939180	03939186	03939181	03939185	03939187	03939190
Ports	2	2	4	4	6	6	Additional 2
L (mm)	73.4	73.4	133.4	133.4	193.4	193.4	-
H (mm)	90	150.8	90	150.8	90	150.8	-

## STYLI CHANGER RACK FOR SCANNING PROBES HP-S-X1H/S

### HR-X1-TR



Driving significant cycle time reductions, the HR-X1-TR is attached vertically on the guideway support of the machine and moves with the moving portal of the machine. Unlike a styli changer rack fixed to the base of the machine, the measurement volume isn't reduced with this vertical rack.

The HR-X1-TR can be used together with HP-S-X1S or HP-S-X1H scanning probes. The HR-X1-TR is available with different sizes of magazine strips.

Part no.	Part description	Z-axis	Max. ports
M00-398-201-000	HR-X1-TR	300	2
M00-295-201-000		600	4
M00-304-201-000		700	4
M00-304-201-000		900	5
M00-304-201-200	Styli port		
M00-398-201-200	Styli port for machine 543		



## STYLI CHANGER RACK FOR SCANNING PROBES HP-S-X1C/H/S AND HP-S-X3

HR-X



The styli changer rack HR-X saves time and reduces manual interventions by enabling quick changes of styli configurations within a measuring program. The HR-X is suitable for Hexagon Reference and GLOBAL coordinate measuring machines in a range of sizes. Depending on the scanning probe and the ambient conditions, there are different ports for the styli changer rack HR-X.

Part no.	Size CMM	Width (mm)	Height (mm)	Compatibility		
				HP-S-X1H HP-S-X1S	HP-S-X1C	HP-S-X3
M00-1087-010-000	5.4.3	400	195	X	(X)	-
M00-1087-012-000	5.4.3	400	295	-	X	X
M00-1087-015-000	7.5.5	400	295	X	X	X
M00-1087-020-000	7.7.5	700	295	X	X	(X)
M00-1087-022-000	7.7.5	700	395	(X)	(X)	X
M00-1087-020-000	10.7.6	700	295	X	X	(X)
M00-1087-022-000	10.7.6	700	395	(X)	(X)	X
M00-1087-030-000	15.9.7	900	295	X	X	(X)
M00-1087-032-000	15.9.7	900	395	(X)	(X)	X
M00-1087-035-000	20.9.7	900	295	X	X	(X)
M00-1087-037-000	20.9.7	900	395	(X)	(X)	X
M00-1087-040-000	xx.12.10	1200	395	X	X	X

(X) represents an alternatively selectable stylus rack

Stylus changer ports or stylus clamping/holders are not included in any styli changer rack and have to be ordered additionally.

## STYLI CHANGER RACK PORTS FOR HP-S-X1 AND HP-S-X3 HR-X



M00-114-113-000  
Styli port



M00-114-167-000  
Styli port shopfloor



M00-114-213-000  
Styli port triple



M00-114-109-000  
Styli receptacle

Depending on the size of the scanning probe and the ambient conditions, there are different ports for the styli changer rack HR-X.

Max. stylus changer ports	HP-X1-P	HP-X1-P-SF	HP-X1-3P	HP-X3-P
Part no.	M00-114-113-000	M00-114-167-000	M00-114-213-000	M00-114-109-000
M00-1087-010-000	9	9	3	-
M00-1087-012-000	9	9	3	6
M00-1087-015-000	9	9	3	5
M00-1087-020-000	17	17	5	9
M00-1087-022-000	17	17	5	9
M00-1087-030-000	22	22	7	12
M00-1087-032-000	22	22	7	12
M00-1087-035-000	22	22	7	12
M00-1087-037-000	22	22	7	12
M00-1087-040-000	29	29	9	17

## STYLI CHANGER RACK AND EXTENSION RACK FOR SCANNING PROBE HP-S-X5

HR-XS | HR-XS-EX



The styli changer rack HR-XS (main rack) allows for fast change of styli configurations within a measuring program. The styli changer rack HR-XS is suitable for Hexagon Reference and GLOBAL coordinate measuring machines (depending on the size of the CMM).

Increasing measuring flexibility, the HR-XS-EX extension rack allows for an additional three ports. An already installed styli changer rack HR-XS is required for the use of the extension rack.

HR-XS Main Rack	HR-XS-EX Extension Rack	SIZE CMM Reference / GLOBAL CMMs
M00-1087-110-000	M00-1087-115-000	10.7.6
M00-1087-120-000	M00-1087-125-000	15.9.7
M00-1087-130-000	M00-1087-135-000	20.9.7
M00-1087-140-000	M00-1087-145-000	xx.12.10

## STYLI CHANGER RACK PORTS

HR-XS -P | HR-XS-P-X



M00-153-285-000




M00-153-286-000

Different styli ports can be used for the HR-XS styli changer rack to cater for different scanning probes and the user's desired position for the styli changer rack.

SCANNING PROBE HP-S-X5	SIZE CMM		HR-XS-P	HR-XS-P-X
	Width (mm)	Hight (mm)	M00-153-285-000	M00-153-286-000
			Max. stylus changer ports Styli receptacle in Y	Styli receptacle in X
M00-1087-110-000	700	415	8	6
M00-1087-115-000	700	155	8	-
M00-1087-120-000	900	515	11	8
M00-1087-125-000	900	155	11	-
M00-1087-130-000	900	515	11	8
M00-1087-135-000	900	155	11	-
M00-1087-140-000	1200	515	14	10
M00-1087-040-000	1200	155	14	-

### 3RD AXIS ADAPTER

HH-ACW-3AA





The HA-ACW-3AA 3rd axis adapter allows for the correct application of non-contact sensors in combination with the HH-ACW-43MW. Driving high speed operation, the repeatable docking capability allows the adapter to change both manually or in automatic mode by using the HR-ACW-AC probe changer rack.

HA-ACW-3AA	
Part No.	G30414900
Useful angular stroke	± 180°
Rotation speed	1 rad/sec.
Acceleration	10 rad/sec.
Resolution	3.16 arc
Positioning repeatability	7 x 10 rad
Weight	1.7 Kg
Max. tool weight	1 kg
Max. applied torque	1.5 Nm
Probe changer rack	HR-ACW-AO
Compatible sensors	HP-L

### ADAPTER HA-ACW-AA

EXTENSION HA-ACW200M/330M/570M




Maximising measurement versatility, the HA-ACW-AA adapter enables the use of all Hexagon probes/extensions equipped with an autojoint connection. The repeatable docking allows users to change the adapter in automatic mode or manual mode by using the HA-ACW-AC probe changer rack.

The series of extensions – available in three different lengths – can be used with all point-to-point probes equipped with an M8 thread. The repeatable docking system allows for automatic and manual change of extensions.

HA-ACW	Part No.	Material	L (mm)	Weight (g)
HA-ACW-AA (Adapter)	G32026300	Aluminium alloy / Carbon fibre	129.5	500
HA-ACW-200M (Extension)	G32005800	Aluminium alloy / Carbon fibre	200	500
HA-ACW-330M (Extension)	G32005900	Aluminium alloy / Carbon fibre	320	600
HA-ACW-570M (Extension)	G32026000	Aluminium alloy / Carbon fibre	570	650
Extension Kit	G32026200			

## TKJ TO M8 ADAPTERS

HA-TM



The HA-TM adapters, available in four different lengths, are suitable for all Hexagon touch-trigger probes with M8 threads. The TKJ to M8 adapters allows fast and repeatable probe mounting and dismounting in automatic mode in combination with the HR-R probe changer rack. Changing the probes manually is also possible.

TKJ to M8 ADAPTERS	Part No.	Material	L (mm)	Weight (g)
HA-TM-31	03939356	Aluminium / Stainless steel	33	64
HA-TM-140	03939366	Aluminium / Stainless steel	140	84
HA-TM-300	03939367	Aluminium / Stainless steel	300	121
HA-TM-450C	03939368	Carbon fibre / Stainless steel	450	150

## FIXED ADAPTER

HA-F




The HA-F fixed adapter allows any autojoint multiwire probe to be used with the HH-A-T and HH-AS-T probe head series. The HA-F is fully compatible with the HR-R probe changer rack.

FIXED ADAPTER	Part No.	Material	L (mm)	Weight (g)
HA-F	03969369	Stainless steel	35 mm	75 g

## TKJ ADAPTER

HA-TT




The HA-TT series is a range of extensions and TKJ to TKJ angular adapters. The extensions allow for the use of long stable probe builds for deep measuring applications. The range also contains four angular adapters that enable the probing product to be mounted at a variety of angles. Each adapter contains a full multiwire and is fully compatible with the HR-R probe changer rack.

TKJ EXTENSIONS   ADAPTERS	Part No.	Material	L (mm)	Weight (g)	Angular °
HA-TT-50 Extension	03939360	Aluminium / Stainless steel	52	80	
HA-TT-100 Extension	03939361	Aluminium / Stainless steel	102	102	
HA-TT-200 Extension	03939362	Aluminium / Stainless steel	202	153	
HA-TT-300 Extension	03939363	Aluminium / Stainless steel	302	200	
HA-TT-300C Extension	03939364	Carbon fibre / Stainless steel	302	-	
HA-TT-A0 Angular Adapter	03939390	Aluminium / Stainless steel	35	71	0°
HA-TT-A30 Angular Adapter	03939391	Aluminium / Stainless steel	35	71	30°
HA-TT-A60 Angular Adapter	03939392	Aluminium / Stainless steel	35	71	60°
HA-TT-A90 Angular Adapter	03939393	Aluminium / Stainless steel	35	71	90°
Set of 4 TKJ Angular Adapter	03969394				

## M8 EXTENSIONS

### HA-M




The HA-M series is a range of M8 to M8 threaded connectors enabling deep part access. The extension can be mounted on the HH-MI-M, HH-A-M or HA-TM series of probe heads or accessories. The extensions are available in three sizes: 50, 100 and 200 mm. A HA-M KIT includes all three lengths.

M8 EXTENSIONS	Part No.	Material	L (mm)	Weight (g)
HA-M KIT	03969077	Aluminium		
HA-M-50	03939065	Aluminium	50	23
HA-M-100	03939066	Aluminium	100	55
HA-M-200	03939067	Aluminium	200	85

## HDKJ TO TKJ ADAPTERS

### HA-HT




The HA-HT series is a range of HDKJ to TKJ adapters, enabling the use of long stable probe builds for deep measuring applications. Each adapter contains a full multiwire and is fully compatible with the HR-R probe changer rack equipped with a HR-RH module.

HDKJ TO TKJ ADAPTERS	Part No.	Material	L (mm)	Weight (g)
HA-HT-CA	03969345	Aluminium / Stainless steel	58	170
HA-HT-150	03939346	Aluminium / Stainless steel	150	220
HA-HT-300C	03939347	Carbon fibre	300	260

## HDKJ TO M8 ADAPTERS

### HA-HM



The HA-HM series is a range of HDKJ to M8 adapters, compatible with any touch trigger probe fitted with an M8 connector. HA-HM adapters allow for the use of extremely long and stable probe builds for very deep measuring applications. The adapter is fully compatible with the HR-R probe changer rack equipped with a HR-RH module.

HDKJ TO M8 ADAPTERS	Part No.	Material	L (mm)	Weight (g)
HA-HM-CA	03939395	Aluminium / Stainless steel	44,5	170
HA-HM-250C	03939396	Carbon fibre	250	200
HA-HM-500C	03939397	Carbon fibre	500	250
HA-HM-750C	03939398	Carbon fibre	750	300

## ADDITIONAL STYLI PORTS



060-691.492-000  
\*Receptacle PMM  
Weight: 240 g



M00-114-112-000  
\*Receptacle




M00-114-111-000  
\*Receptacle



M00-114-110-000  
\*Receptacle

\* not compatible with stylus racks HR-X, HR-XS, HR-XS-EX

## REFERENCE SPHERES



M00-153-270-000, M8  
Ceramic, with stand,  
Ø 30 mm



M00-153-271-000, M8  
Ceramic, without stand,  
Ø 30 mm



M00-398-270-000  
Ceramic, with stand,  
Ø 15 mm, M4



M00-689-364-000  
Ceramic, without stand,  
Ø 25 mm, M6

M00-314-270-000,  
Ceramic, with stand,  
Ø 30 mm, M8  
for Leitz Infinity

M00-398-271-000  
Ceramic, without  
stand, Ø 15 mm, M4




060-694.021-011  
Tommy bar 100 x 3 mm




M07-S02-000-012  
Chamois leather



# AUTOMATIC PROBE HEADS




\* To ensure compatibility with the system, please check individual machine configuration or data sheet.



# CONTINUOUS PROBE HEADS


HH-ACW-43MW



\* To ensure compatibility with the system, please check individual machine configuration or data sheet.

**SCANNING PROBES**

HP-S-X1C | HP-S-X3 | HP-S-X5



\* To ensure compatibility with the system, please check individual machine configuration or data sheet.

## HH-T

### CONTENTS OF SETS

	047714	Built-in	Built-in	Built-in	Built-in	03969302	03969303	03969304	03969044	03969045	03969046
	d9,5mm Shaft	DIN 5 Pin Connection	Sub-D HD 15 Pin Connection	Sub-D 15 Pin Connection	LEMO 14 Pin Connection	M3 Stylus 2 x 21mm	M3 Stylus 3 x 21mm	M3 Stylus 4 x 21mm	M3 Extension L10mm	M3 Extension L20mm	Star stylus Holder
03939019		X				X					
03939020	X	X				X					
03939021	X	X				X	X	X	X	X	X
03939024	X				X	X					
03939025	X			X		X					
03939027	X		X			X					

## HH-MI

### CONTENTS OF SETS AND ADDITIONAL ACCESSORIES

		Cable DIN 5 Pin	M3 Stylus 4 x 21mm	D20mm Shaftadapter	Cable DIN-DIN	Cable Sub-D 15 Pin	Cable Sub-D, 15 Pin HD
		03969071	03969304	051555	03969071	03969073	03969074
HH-MI	03939030	X	X				
HH-MI	03939103	X	X	X			
HH-MI-M	03939031	X					

## HH-AS

### AVAILABLE ADAPTERS

		Built-in	Sub-D 15 Pin	Adapter Sub-D HD15 pin Sheffield	Adapter LEMO 14 Pin L300mm	Adapter Sub-D HD15 Pin
				03960289	03960290	03960291
HH-AS8-T5	03939270	X				
HH-AS8-T5	03939260	X				
HH-AS8-T7.5	03939362	X				
HH-AS8-T2.5	03939422	X				
HH-AS8-H2.5	03939431	X				
HH-AS8-M5	03939290	X				
HH-AS6-M5	03939280	X				
HH-AS8-M7.5	03939363	X				

**HH-A**  
CONTENTS OF SETS

		Flange HH-A to DEA 03939382	Flange HH-A -2.5 to DEA 03939383	Ø 9.5mm Shank for HH-A 03939370	Ø 20mm S Shank for HH-A 03939371	Ø 12mm Shank for HH-A 03939372	Sub-D HD 15 Pin 03939065	Sub-D 15 Pin 03939066	LEMO 14 Pin 03939067	Sub-D HD 15 Pin Sheffield 03939068	LEMO 14 Pin L300mm 03939069	PROBE HEAD
HH-A-T5	03939450											X
HH-A-T5	03939051			X			X					X
HH-A-T5	03939052				X			X				X
HH-A-T5	03939053							X				X
HH-A-T5	03939054			X				X				X
HH-A-T5	03939055	X						X				X
HH-A-T5	03939056			X						X		X
HH-A-T5	03939057	X								X		X
HH-A-T5	03939059					X					X	X
HH-A-M5	03939400											X
HH-A-M5	03939201			X			X					X
HH-A-M5	03939202			X				X				X
HH-A-M5	03939203	X							X			X
HH-A-M5	03939205	X						X				X
HH-A-T7.5	03939360											X
HH-A-T7.5	03939365			X			X					X
HH-A-T7.5	03939366			X				X				X
HH-A-T7.5	03939367			X						X		X
HH-A-T7.5	03939368	X						X				X
HH-A-M7.5	03939361											X
HH-A-M7.5	03939375			X			X					X
HH-A-M7.5	03939376			X				X				X
HH-A-M7.5	03939377			X						X		X
HH-A-M7.5	03939378	X						X				X
HH-A-T2.5	03939420						Cables and Shanks sold separately					
HH-A-H2.5	03939430						Cables and Shanks sold separately					



# HEXAGON

MANUFACTURING INTELLIGENCE

Hexagon Manufacturing Intelligence helps industrial manufacturers develop the disruptive technologies of today and the life-changing products of tomorrow. As a leading metrology and manufacturing solution specialist, our expertise in sensing, thinking and acting – the collection, analysis and active use of measurement data – gives our customers the confidence to increase production speed and accelerate productivity while enhancing product quality.

Through a network of local service centres, production facilities and commercial operations across five continents, we are shaping smart change in manufacturing to build a world where quality drives productivity. For more information, visit [HexagonMI.com](https://www.hexagonmi.com).

Hexagon Manufacturing Intelligence is part of Hexagon (Nasdaq Stockholm: HEXA B; [hexagon.com](https://www.hexagon.com)), a leading global provider of information technologies that drive quality and productivity across geospatial and industrial enterprise applications.



COORDINATE MEASURING MACHINES



3D LASER SCANNING



SENSORS



PORTABLE MEASURING ARMS



SERVICES



LASER TRACKERS & STATIONS



MULTISENSOR & OPTICAL SYSTEMS



WHITE LIGHT SCANNERS



METROLOGY SOFTWARE SOLUTIONS



CAD / CAM



STATISTICAL PROCESS CONTROL



AUTOMATED APPLICATIONS



MICROMETERS, CALIPERS AND GAUGES



DESIGN AND COSTING SOFTWARE